

GLAND ACCESSORIES 06

STOPPING PLUGS

FLAMEPROOF
ZONE 1,2,21,22



SPECIFICATION

TYPE	Stopping Plugs type 800
APPLICATION	Stopping Plugs are used to close unused entries
HAZARDOUS AREA ZONE	Zone 1 - Zone 2 (Gas) Zone 21 - Zone 22 (Dust)
MARKING	Ex II 2 G D Ex d IIC Gb Ex e IIC Gb Ex t IIIC Db
STANDARDS	EN60079-0 EN60079-1 EN60079-7 EN60079-31
EU-TYPE EXAMINATION CERTIFICATE NO.	TÜV 11 ATEX 7156 X
INGRESS PROTECTION	IP66
MATERIAL	Brass or Stainless Steel
FINISH	Nickel Plating (for brass)
OPERATING CONDITION	Indoor/Out door
ORDERING DETAILS	Sealing Washer Locknut

DIMENSIONS (MM)

SIZE	ACROSS CORNER	ACROSS FLAT (MIN)
M20	Text	24.0
M25	33.3	30.0
M32	39.9	36.0
M40	49.9	44.0
M50	61.0	55.0
M63	77.6	68.0
M75	90.3	80.0
M90	113.0	100.0

* For other thread forms, equivalent thread size corresponding to ISO metric should be used

