

Golnoor Lighting Group
2nd Floor, No. 4, Mahtab Bldg., 21st Lane.,
Mirza Shirazi St., Mottahari St, Tehran, Iran
Tel : +98-21-88864780-81
Web : www.golnoor.com

PRO FORMA INVOICE

Date: 2025/AUG/09
Expiration Date : 2025/AUG/19
Invoice No: TP-04-233-REV03

Customer Identification:

Customer Name :	Adish Co.
Sales Conduct person:	Ms. Moradi

Description of Sales :

No	Description	Qty	Unit Price (Rial)	Total Price (Rial)
1	Type: Proxima (9cm) Power: 60W Degree of protection: IP42 Body: Aluminum Mounting: Recessed Mounted Power factor: 0.95 Voltage: 230/50 Luminous Flux: 5700 lm Color Temperature: 6500 k Dimension: L1700xW90xH90 Without Cable gland Without Junction Box With Throughwiring capability Providing cable gland for this lighting fixture is not possible. As per attached catalogue Origin: Golnoor/Iran	31	***	***
2	LED Industrial Lighting Fixture Type: Atlas Type of Mounting: Wall Mounted Body: Aluminum Degree of Protection: IP65 Power: 36 w Power factor: 0.95 Luman Flux: 4700 lm Temperature ambient: -20 to +50°C Entry: 2*M20 Cable gland: 2*M20 CABLE GLAND SUITABLE FOR ARMORED CABLE Color Temperature: 6500 k Origin: Golnoor/ Iran As per attached catalogue You are kindly requested to check the Inner sheath & outer sheath of proposed cable gland: Inner sheath (Min-Max) of armored M20L (10.0-15.5) Outer sheath (Min-Max) of armored M20L (13.5-20.5)	4	***	***
3	LED Type Lighting fixture Type: Parmida Power: 40W Degree of protection: IP42 Body: polymer Mounting: recessed Mounted Power factor: 0.95 Voltage: 230/50 Dimonsion: 60*60 Luminous Flux: 5000 lm Color Temperature: 4000 k Without Junction box Without Cable gland (Providing cable gland for this lighting fixture is not possible.) As per attached catalogue Origin: Golnoor/Iran	17	***	***

دفتر تهران:

خیابان مطهری، میرزای شیرازی، کوچه ۲۱، ساختمان مهتاب
طبقه دوم، شماره ۶ کد پستی: ۱۵۸۶۶-۸۵۷۱۷
تلفن: ۰۲۱-۸۸۸۶۴۷۸۰،۱ فکس: ۰۲۱-۸۸۱۴۰۳۵۱

دفتر مرکزی:

اصفهان، پل فردوسی، ابتدای خیابان شیخ صدوق شمالی،
نبش بن بست الهیه، پلاک ۹ کد پستی: ۸۱۶۳۶-۵۴۷۵۳
تلفن: ۰۳۱-۳۷۱۷۷ فکس: ۰۳۱-۳۶۶۲۹۴۹۹

4	LED Type Lighting fixture Type: Parmida Power: 60W Degree of protection: IP42 Body: polymer Mounting: Recessed Mounted Power factor: 0.95 Voltage: 230/50 Dimonsion: 60*60 Luminous Flux: 7500 lm Color Temperature: 4000 k Without Junction box Without Cable gland(Providing cable gland for this lighting fixture is not possible.) As per attached catalogue Origin: Golnoor/Iran	34	***	***
5	LED Type Lighting fixture Type: Maral Power: 24W Degree of protection: IP42 Body: Dicast Aluminum Mounting: Surface Mounted Power factor: 0.95< Voltage: 230/50 Luminous Flux: 2640 lm Temprature: 6500 k Cutout_hole_diameter: 160~165 Without CABLE GLAND & JUNCTION BOX(Providing cable gland for this lighting fixture is not possible.) As per attached catalogue Origin: Golnoor/Iran	3	***	***
6	LED Industrial Lighting Fixture Type: Atlas Type of Mounting: Wall Mounted Body: Aluminum Degree of Protectin: IP65 Power: 20 w Power factor: 0.95 Luman Flux: 2150 lm Temperature ambient: -20 to +50°C Entry: 2*M20 Cable gland: 2*M20 CABLE GLAND SUITABLE FOR ARMORED CABLE Color Temperature: 6500 k Origin: Golnoor/ Iran As per attached catalogue You are kindly requested to check the Inner sheath & outer sheath of proposed cable gland: Inner sheath (Min-Max) of armored M20L (10.0-15.5) Outer sheath (Min-Max) of armored M20L (13.5-20.5)	23	***	***
7	LED Type Lighting fixture Type: Maral Power: 24W Degree of protection: IP42 Body: Dicast Aluminum Mounting: Recessed Mounted Power factor: 0.95< Voltage: 230/50 Luminous Flux: 2640 lm Temprature: 6500 k Cutout_hole_diameter: 160~165 Without CABLE GLAND & JUNCTION BOX(Providing cable gland for this lighting fixture is not possible.) As per attached catalogue Origin: Golnoor/Iran	54	***	***

دفتر تهران:

خیابان مطهری، میرزای شیرازی، کوچه ۲۱، ساختمان مهتاب
طبقه دوم، شماره ۶ کد پستی: ۱۵۸۶۶-۸۵۷۱۷
تلفن: ۰۲۱-۸۸۸۶۴۷۸۰، ۰۲۱-۸۸۱۴۰۳۵۱ فکس:

دفتر مرکزی:

اصفهان، پل فردوسی، ابتدای خیابان شیخ صدوق شمالی،
نبش بن بست الهیه، پلاک ۹ کد پستی: ۸۱۶۳۶-۵۴۷۵۳
تلفن: ۰۳۱-۳۷۱۷۷ فکس: ۰۳۱-۳۶۶۲۹۴۹۹

8	LED Flood Lighting fixture Type: Ariel 2 Power: 165 W Degree of protection: IP66 Body: Dicast Aluminum Mounting: Bracket Mounted Beam Angle: 90 Power factor: 0.95 Voltage: 230/50 Luman Flux: 25500 lm Ambiant Temperature: -20 to +50 Color Temperature: 6500 k As per attached catalogue Origin: Golnoor/Iran Note: Lighting fixture gets 1*PG 13.5 Cable between box and fixture doesn't provided Industrial Junction Box Type: GJJB 302 Body: Die-Cast Aluminum Degree of protection: IP66 Color: Ral7024 Drilling: 1*M20 & 1*M25 On bottom side, 1*M20 On top side Nickel Plated Brass Cable gland: 2*M20 suitable for armored cable with shroud & earth tag Nickel plated brass plug: 1*M25 Terminal : 12*RTP 2.5 + 3*RET 2.5 Jumper: 6*CC2 2.5 As per attached Catalogue Origin: Golnoor/Iran You are kindly requested to check the Inner sheath & outer sheath of proposed cable gland: Inner sheath (Min-Max) of armored M20L (10.0-15.5) Outer sheath (Min-Max) of armored M20L (13.5-20.5)	20	***	***
Sub total		***		
Shipment price		EX WORK		
Tax		***		
PAYABLE		***		

► **Quotation Validity: 10 days**


- Delivery Place: Ex-work
- Delivery Time: 40 Working Days
- All Prices Exclude Installation, Erection, Special Tools, Special Packing, Training Expenses, ...etc.
- If required Test and Inspection is done in Vendor's Laboratory, it will be free of charge.
- Payment Terms: 50% in advance and the balance will be paid before delivery of the equipment
- Value-Added Tax would be born by the purchaser

Prepared by
Zahra Kazempour
Sales Engineering Expert



Thanks for your Business !

Confirmed by
Maryam Keyhanifar
Sales Engineering Supervisor



دفتر تهران:

خیابان مطهری، میرزای شیرازی، کوچه ۲۱، ساختمان مهتاب
کد پستی: ۱۵۸۶۶-۸۵۷۱۷
تلفن: ۰۲۱-۸۸۸۶۴۷۸۰، ۰۲۱-۸۸۱۴۰۳۵۱
فکس: ۰۲۱-۸۸۱۴۰۳۵۱

دفتر مرکزی:

اصفهان، پل فردوسی، ابتدای خیابان شیخ صدوق شمالی،
نیش بن بست الهیه، پلاک ۹
کد پستی: ۸۱۶۳۶-۵۴۷۵۳
تلفن: ۰۳۱-۳۷۱۷۷
فکس: ۰۳۱-۳۶۶۲۹۴۹۹